Delock USB Type-C™ Docking Station for 1 x U.2 SSD

Description

This Docking Station by Delock enables an external connection of one **U.2 SSD** through the USB interface.

Supports SuperSpeed USB 10 Gbps

A maximum data transfer rate of up to **USB 3.2 Gen 2** - 10 Gbps can be reached.

Good cooling

The bottom consists of a **stable metal plate with cooling fins**. These provide a passive cooling for the inserted memory.



Specification

- Connectors:
  1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
  1 x U.2 SFF-8639 female
  1 x DC jack
- Chipset: Asmedia ASM2362
- Function key: 1 x On / Off switch
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Supports S.M.A.R.T.
- Supports TRIM
- Supports UASP
- Plug & Play
- Bootable
- Colour: black
- Dimensions (LxWxH): ca. 138 x 80 x 23 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1.5 A
- Output: 12.0 V / 3.0 A
- Ground outside, plus inside
- Dimensions:
  inside: ø ca. 2.1 mm
  outside: ø ca. 5.5 mm
  length: ca. 10 mm

System requirements

- Android 10.0 or above
- Chrome OS
- Linux Kernel 5.11 or above
- Mac OS 11.2.3 or above
- Windows 8.1/8.1-64/10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- PC or laptop with a free USB Type-A port or
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port

Package content

- Docking station
- Cable USB-C™ male to USB-C™ male, length ca. 80 cm

Item no. 63368

EAN: 4043619633685

Country of origin: China


Package: Retail Box

© 2022 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

- Cable USB-C™ male to USB Type-A male, length ca. 80 cm
- External power supply 12.0 V / 3.0 A
- Screws
- User manual

Images









© 2022 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

General	
Function:	Plug & Play bootable TRIM S.M.A.R.T.
Suitable for data medium:	2.5″
Supported operating system:	Android 10.0 or above Chrome OS Surface Pro 7 Windows 10 32-bit Windows 10 64-bit Windows 8.1 32-bit Windows 8.1 64-bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Mac OS 11.2.3 or above Windows 11 Linux Kernel 5.11 or above
Interface	
External:	1 x DC jack 5.5 mm x 2.1 mm 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
Internal:	1 x U.2 SFF-8639 female
Technical characteristics	
Chipset:	Asmedia ASM2362
Data transfer rate:	10 Gbps
Physical characteristics	
Length:	138 mm
Width:	80 mm
Height:	23 mm

© 2022 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.